ALMONARD

RANGE OF WATER PUMPS

Self Priming - Centrifugal Monobloc - Openwell Submersible Pump

ISO 9001:2008

ICR INTERNATIONAL CERTIFICATION REGISTRAR

Certificate No. : QI-4567/07

IS : 8472

ISI

CM / L 7467790

ALMONARD

Self Priming - Centrifugal Monobloc - Openwall Submersible Pump

Almonard Highflow Self Priming (Suction Type) Monobloc Pump

Features : Self Priming (Higher Suction Capacity), Gun Metal Impeller & SS-304 Impeller case. Totally enclosed Fan Cooled Motor.

MODEL	HP	KW	PIPE SIZE (mm)	PIPE SIZE (inch)	SUCTION HEAD Mtrs.	Total Head in Metre / Discharge Ltr. Per Minute								
						5	8	10	12	15	17	20	22	25
HIGH FLOW MINI	01/8	0.12	12 x 12	0.5 x 0.5	6	16	14	13	12	9	-	-	-	-
* HIGH FLOW	0.5	0.37	15 x 15	0.5 x 0.5	8	-	20	20	18	17	14	13	11	7

Application: Domestic use. Minor irrigation. Hotel & appartment.

Almonard Self Priming (Quick Suction) Monobloc Pump

MODEL	HP	KW	PIPE SIZE (mm)	PIPE SIZE (inch)	SUCTION HEAD Mtrs.	Total Head in Metre / Discharge Ltr. Per Minute												
						5	8	10	12	15	17	20	22	25	28	30	35	40
* SUPER	0.5	0.37	25 x 25	1 x 1	8	35	33	31	28	26	23	21	15	13	-	-	-	-
* SUPER GOLD	0.5	0.37	25 x 25	1 x 1	8	40	36	34	30	28	26	24	20	16	-	-	-	-
SUPER STAR	1	0.75	25 x 25	1 x 1	8	-	60	56	54	53	52	48	46	44	42	38	34	30

Application: Domestic use. small irrigation.

Almonard Regenerative Self Priming Monobloc Pump

Features : High Quality Powder Coated, High Quality Extruded Alluminium Motor Body. Forged Brass Impeller. High Quality Mechanical Seal, Vaccum Impregnated Stator Fitted with TOP.

HP	KW	PIPE SIZE (mm)	PIPE SIZE (inch)	Total Head in Metre / Discharge Ltr. Per Minute									
				6	9	12	15	18	24	30	36	42	45
0.25	0.18	20 x 20	0.75 x 0.75	25	21	18	11	7	-	-	-	-	-
* 0.50	0.37	25 x 25	1 x 1	35	32	30	26	24	16	11	-	-	-
1.00	0.75	25 x 25	1 x 1	41	39	37	35	32	-	25	21	18	14

Application: Household Pumping to overhead tanks. Gardening / Fountains, Construction activities. Pressure Boosting Systems.

Almonard Openwell Series

Features : Water Lubricated Carbon Thrust Bearing with Stand Axial Load, Impeller Ideally Designed and dynamically balanced, High Discharge.

MODEL	HP	KW	PIPE SIZE (mm)	PIPE SIZE (inch)	Total Head in Metre / Discharge Ltr. Per Minute											
					5	8	10	12	15	17	20	22	25	28	30	32
AHMP - 1	0.5	0.37	25 x 25	1 x 1	-	140	125	110	75	-	-	-	-	-	-	-
AHMP - 2	1	0.75	32 x 25	1.25 x 1	-	-	-	240	185	160	130	110	70	-	-	-
AHMP - 3	1	0.75	50 x 50	2 x 2	460	405	320	240	-	-	-	-	-	-	-	-
AHMP - 4	1.5	1.1	40 x 40	1.5 x 1.5	-	-	-	250	230	220	195	170	135	90	-	-
AHMP - 5	2	1.5	50 x 50	2 x 2	-	-	-	340	305	275	245	205	165	-	-	-
AHMP - 6	2	1.5	75 x 75	3 x 3	900	810	700	650	450	-	-	-	-	-	-	-
AHMP - 7	3	2.2	50 x 50	2 x 2	-	-	-	-	-	-	400	370	325	240	160	100

Application: Domestic water supply, Over head tank, industrial water Sources, Small Farms

Note : Also Available 3.00 HP, 10.00 HP Openwell Submersible Pump

REGD. TRADE MARK

ALMONARD PRIVATE LIMITED

305, Kakad Chambers, 3rd Floor, 132, Dr. Annie Besant Road, Worli, Mumbai - 400 018. Tel. : 2492 6552, 2490 3094, 2490 3463, 2490 2269, Fax : 022-2490 3760 Email : almonard@bom7.vsnl.net.in

BARODA WORKS : 852/2 & 853/1, GIDC, Makarpura, BARODA - 390 010. Tel.: 2633264 Fax : 2656330

CHENNAI Off. & Works : 439/3B, Ekambara Naicker Industrial Estate, Off Arcot Road, Alapakkam, Porur, Chennai - 600 116. Tel. : 2476 2100, 2476 2030 Fax : 2476 2627 E-mail : almonard@md5.vsnl.net.in

BRANCHES

AHMEDABAD • BANGALORE • BHUBANESHWAR • CALICUT • COCHIN • COIMBATORE • DELHI • INDORE • JAIPUR • JALANDHAR • KANPUR • MADURAI • NAGPUR • PUNE • SECUNDERABAD